

FORCED-AIR FLASH CURE UNIT

AIR-FLASH

A 140 CFM blower draws air through an oversized filtered intake, sends it through an air diverter, then distributes it evenly across the entire heater face.

The heat and air flow are both adjustable.

Add an AutoFlash for the most versatile flash cure in the industry!



Adjustable air flow keeps skin cool in any position.



AIR-FLASH 18
Shown with Standard Stand

CE Certified

RA-18-240

RA-1824

Heater Size

18" x 18" (46 x 61cm)

18" x 24" (46 x 61cm)

Power (Wattage)

3,500w @ 240v

4,300w @ 240v

Power Plug

NEMA 6-20P*

NEMA L6-30P* (Sold separate)

Features

- RELIABLE** 15 Year Heater Warranty
- POWERFUL** 3500 watt (18 x 18) or 4300 watt (18 x 24) heater
- VERSATILE** Air only, full heat and air, or modulate air velocity and heat.
- SMART** Adjustable heat shield helps maintain heater surface consistency
- CLEAN** Large filtered air intake delivers clean air to heater

- ADJUSTABLE** Heat, air speed, heat shield, height and level
- EFFICIENT** Air cooled outer skin and side handles
- FAST** Flash plastisol in as little as 4 seconds
- CONVENIENT** Heavy duty side handles & locking casters

Options



AutoFlash add

Super Heavy Duty Stand



Rotary Table

*Domestic plugs listed. International cords available.



AIR-Flash_0512

Flash Cure Units

Technical Specifications



TUV-ISO 9001-2000
Compliant

	F-100	F-1000	REDFLASH		AIR-FLASH	
Models	F-100	F-1000	R-18-240	R-1824-240	RA-18-HO	RA-1824
Heater Warranty	15 Year	15 Year	15 Year	15 Year	15 Year	15 Year
Bumper to Bumper Warranty	3 Year	3 Year	3 Year	3 Year	3 Year	3 Year
Heater Size	16" x 16" (41 x 41 cm)	18" x 18" (46 x 46 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)	18" x 18" (46 x 46 cm)	18" x 24" (46 x 61 cm)
Unit Warm Up Time	15 min. (120V) or 10 min. (240V)	20 min. (120V) or 10 min (240V)	6 min.	12 min.	6-10 min	6-10 min
Heater Wattage	1625 Watt Heater	1950 Watt Heater	2600 or 3500 Watt Heater	3500 Watt Heater	3500 Watt Heater	4300 Watt Heater
Electrical Specs* / included plug (Some models require a dedicated line. 50/60 HZ for all units.)	120V/13A/1625W NEMA 5-15P 240V/6.5A/1625W NEMA 6-15-P	120V/15.6/1950W NEMA 5-20P 240V/7.8A/1950W NEMA 6-15-P	240V/9A/2600W NEMA 6-15P 240V/16A/3500W NEMA 6-20P	240V/16A/3500W/ NEMA 6-20P Plug	240V/16A/2500W NEMA 6-10P	240V/19A/4300W/ NEMA L6-30P
Electrical Specs - AutoFlash / included plug	110-125V/1A/NEMA 5-15P 220-240V/1A/NEMA 6-15P					

Shipping Weights and Dimensions

	Weight**	Dimensions**
F-100 (Head and Stand)	39 lbs (18 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)
F-1000 (Head and Stand)	42 lbs (19 kg)	23" x 28" x 9" (58 x 71 x 22.9 cm)
R-18-240 (Head Only)	35 lbs (16 kg)	26" x 29" x 7" (66 x 74 x 18 cm)
R-1824-240 (Head Only)	43 lbs (19.5 kg)	26" x 35" x 8" (66 x 90 x 20 cm)
RA-18-HO (Head Only)	64 lbs (29 kg)	29" x 26" x 15" (74 x 66 x 38 cm)
RA-1824 (Head Only)	74 lbs (35.5 kg)	35" x 29" x 15" (89 x 74 x 38 cm)
AF-120/AF-240 AutoFlash kit	51 lbs (25 kg)	31" x 22" x 14" (79 x 56 x 36 cm)
SH-STAND-WS Standard Stand for Manual Flash	22 lbs (10 kg)	37" x 7" x 3" (94 x 18 x 8 cm)
SHHD-STAND-M Heavy Duty Stand for Manual Flash	42 lbs (19kg)	30" x 14" x 7" (76 x 35.5 x 18 cm)
SH-LEGS-AF Standard Stand for AutoFlash	15 lbs (7 kg)	37" x 7" x 3" (94 x 18 x 8 cm)
SHHD-STAND Heavy Duty Stand for AutoFlash	39 lbs (18 kg)	30" x 15" x 11" (76 x 38 x 28 cm)

NORTH AMERICAN POWER PLUG CONFIGURATION		
RECEPTACLE		PLUG
	120V	
NEMA 5-15R		NEMA 5-15P
	240V	
NEMA 5-20R		NEMA 5-20P
NEMA 6-15R		NEMA 6-15P
NEMA 6-20R		NEMA 6-20P
NEMA 6-30LR		NEMA 6-30LP

*If extension cord is required, consult a licensed electrician.

**All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications.

1 in = 2.54 cm
1 lb = 0.454 kg

